

GRAVITY

Stick Plus Vinyl Residential & Commercial Flooring Tile

PRODUCT SPECIFICATION

Total Thickness	EN 428	mm	3.0-4.0
Wear Layer	EN 429	m	0.3-0.55
Weight	EN 430	g/m ²	Approx. 7550

CLASSIFICATION

Classification (Commercial)	EN 649	Class	33
Classification (Industrial)	EN 649	Class	42
Fire Rating	EN 13501-1:2007	Class	Bfl-s1
Slip Resistance	DIN 51130:2004	Class	R10
Slip Resistance	EN 138893	Class	DS
Formaldehyde Emission	EN 14041	Class	E1

PRODUCT PERFORMANCE

Wear Resistance	ISO 24388-A	Cycles	>4000
Permanent Impression	EN 433	mm	<0.1
Dimension Stability	ISO 23999		Pass
Stain Resistance	EN 423		Excellent
Color Fastness	ISO 105 B02		>6
Furniture Feet Displacement	EN 424		No Change
Castor Chairs Influence	ISO 4918		No Damage
Thermal Resistance	EN 12667	m ² K/W	0.035
Impact Sound Reduction	ISO 717/2	db	7
TVOC 28 Days		µg/m ³	<55

CUSTOMIZABLE FUNCTION

Cigarette Protect			Excellent
-------------------	--	--	-----------