

BARNETT SD

Static Dissipative Homogeneous Vinyl Tile

PRODUCT SPECIFICATION

Total Thickness	EN 428	mm	2.0/3.0
Dimension	EN 426	m	0.6*0.6

PRODUCT PERFORMANCE

System Electric Resistance	SJ/T11236-2001	-	$10^6 < \Omega < 10^9$
Exhaustion stage of Static Voltage	SJ/T10694-2006	s	< 2
Friction Electric Voltage	SJ/T11236-2001	V	< 100
Abrasion Resistance	SJ/T11236-2001	g/cm ²	≤0.02
Fire Rating	EN 13501	-	Bfl-s1
Combustion Performance	SJ/T11236-2001	-	FV-0
Smoke Toxicity	GB8624-2006	-	ZA ₃
Anti Bacterial	ISO 22196	-	Rate I
Slip Resistance	DIN 51130	-	R9
Formaldehyde Emission	EN 717-1	-	ND
Residual Indentation	EN 433	mm	≤0.1
Castor Chair Effect	EN 425	-	No effect
Dimension Stability	EN 434	%	≤0.4
Color Fastness	EN ISO 105 B02	-	6
Sound Absorption	EN ISO 0717/2	dB	Approx. 2
Stain Resistance	EN 423	-	No effect